Application No. 09/955,278 Inventor(s): John S. Wang, et al. Title: METHOD AND APPARATUS FOR IMPROVED HIGH-SPEED ADAPTIVE EQUALIZATION Sheet 1 of 12

Replacement Drawings






FIG. 1 (Prior Art)

Application No. 09/955,278 Inventor(s): John S. Wang, et al. Title: METHOD AND APPARATUS FOR IMPROVED HIGH-SPEED ADAPTIVE EQUALIZATION Sheet 2 of 12

Replacement Drawings




FIG. 2A (Prior Art)

Application No. 09/955,278
Inventor(s): John S. Wang, et al.
Title: METHOD AND APPARATUS FOR
IMPROVED HIGH-SPEED ADAPTIVE
EQUALIZATION
Sheet 3 of 12
Replacement Drawings





FIG. 2B (Prior Art)


Application No. 09/955,278
Inventor(s): John S. Wang, et al.
Title: METHOD AND APPÄRATUS FOR
IMPROVED HIGH-SPEED ADAPTIVE
EQUALIZATION
Sheet 4 of 12
Replacement Drawings



Application No. 09/955,278 Inventor(s): John S. Wang, et al. Title: METHOD AND APPARATUS FOR IMPROVED HIGH-SPEED ADAPTIVE EQUALIZATION Sheet 5 of 12

Replacement Drawings

5/12



Replacement Drawings




FIG. 5

Application No. 09/955,278
Inventor(s): John S. Wang, et al.
Title: METHOD AND APPARATUS FOR
IMPROVED HIGH-SPEED ADAPTIVE
EQUALIZATION
Sheet 7 of 12
Replacement Drawings




FIG. 6

Application No. 09/955,278
Inventor(s): John S. Wang, et al.
Title: METHOD AND APPARATUS FOR
IMPROVED HIGH-SPEED ADAPTIVE
EQUALIZATION
Sheet 8 of 12

Replacement Drawings

8/12

Optionally, the process begins when one or more control algorithms are activated or selected (Step 400).



Optionally, the process continues when one or more controllable analog filters are initialized (Step 410).



One or more data signal inputs are received by one or more controllable analog filters (Step 420).



One or more controllable analog filters filter one or more input data signals (Step 430).



One or more filtered data signals are carried on one or more controllable analog filter outputs (Step 440).

FIG. 7A

Application No. 09/955,278 Inventor(s): John S. Wang, et al. Title: METHOD AND APPÄRATUS FOR IMPROVED HIGH-SPEED ADAPTIVE EQUALIZATION

Sheet 9 of 12
Replacement Drawings

9/12

Preferably, one or more error generators receive filtered data signal output signals (Step 450).



Preferably, an error generator may assess the performance of one or more analog filters according to one or more error functions and generate one or more error generator output signals (Step 460).



Preferably, error generator output signals are further processed (Step 470).



Preferably, one or more equalizer controllers receives one or more processed signals (Step 480).



The equalizer controller may compute a new set of coefficients according to one or more error minimization algorithms (Step 490).

FIG. 7B

Application No. 09/955,278
Inventor(s): John S. Wang, et al.
Title: METHOD AND APPARATUS FOR
IMPROVED HIGH-SPEED ADAPTIVE
EQUALIZATION
Sheet 10 of 12

Replacement Drawings

10/12

One or more equalizer controllers control the controllable analog filter by providing control signal inputs that are used to change controllable analog filter coefficients (Step 500).



Optionally, iterate one or more times by returning to Step 420 (Step 510).

Application No. 09/955,278 Inventor(s): John S. Wang, et al. Title: METHOD AND APPARATUS FOR IMPROVED HIGH-SPEED ADAPTIVE EQUALIZATION

Sheet 11 of 12

Replacement Drawings

11/12

The initial filter coefficients may be set to: c(1)=0, c(2)=0, c(3)=0...c(N-1)=0, c(N)=1.0. (Step 600).



An initial error signal may be acquired from the ADC 207 and assigned to a variable, x (Step 610).



Set variable i = 1 (Step 615).



Coefficient c(i) in the controllable analog filter may be set to c(i) + Δ where Δ is a small number.



Acquire a new error signal collected with controllable analog filter set to the new c(i) value and call this error signal value x(i) (Step 630).



Restore the value of c(i) in the controllable analog filter back to its original value $(c(i) - \Delta)$ and increment i (Step 640).

if $i \leq N$

if
i > N
go to Step 650

FIG. 8A

Application No. 09/955,278
Inventor(s): John S. Wang, et al.
Title: METHOD AND APPARATUS FOR
IMPROVED HIGH-SPEED ADAPTIVE
EQUALIZATION
Sheet 12 of 12

Replacement Drawings

12/12

Compute the gradient vector (Step 650).



Perform a line search to find the value of t that minimizes the error signal for coefficient values $[c(1)\ c(2)\ ...\ c(N)]$ - t * $[g(1)\ g(2)\ ...\ g(N)]$ for t >=0. The notation $[c(1)\ c(2)\ ...\ c(N)]$ denotes the N-dimensional vector whose i'th component is c(i) (Step 660).



Validate results and discard invalid results (Step 665).



Set the coefficients for the controllable analog filter to: $[c(1) \ c(2) \ ... \ c(N)] = [c(1) \ c(2) \ ... \ c(N)] - t_{min} * [g(1) \ g(2) \ ... \ g(N)],$ where tmin is the value of t determined according to the line search executed in Step 660 (Step 670).



Optionally, return to Step 610 (Step 680).

FIG. 8B